



747 Douglas Road ▪ PO Box 100  
 Bremen, IN 46506  
 Phone: 800-325-5746 ▪ Fax: 574-546-5379

## ET 1720 **POWER-MAX 50 CETANE** PREMIUM DETERGENCY AND 50 CETANE BOOST

**POWER-MAX 50 CETANE** is a multi-functional additive formulated to boost typical fuels to 50 Cetane or better. It contains outstanding detergent cleaning power three times more effective than detergents used in the former L10 testing procedure. **POWER-MAX 50 CETANE** contains a next-generation anti-foulant that vastly improves the performance of ULSD in newer model vehicles equipped with HPFI (High-Pressure Fuel Injection) systems.

**POWER-MAX 50 CETANE** will re-establish the thermal and oxidation stability of ULSD and will prevent the formation of black sludge that plugs fuel filters. **POWER-MAX 50 CETANE** will clean up hard carbon deposits in fuel injectors and vastly extends filter life.

**POWER-MAX 50 CETANE** is formulated with next gen lubricity additives and Cetane improvers that will raise the Cetane of typical fuels to 50 points or higher. **POWER-MAX 50 CETANE** is formulated to be used in BIO-DIESEL BLENDS as well. Proper treatment with **POWER-MAX 50 CETANE** will vastly extend filter life, restore injector cleanliness, restore lost power and increase fuel economy.

### *Formulated for Ultra Low Sulfur Diesel Fuels & Bio-Diesel Fuels*

#### USER BENEFITS

- Raises Cetane to 50 points or higher (even hard to treat fuels)
- Prevents filter plugging caused by thermal stressing of the fuel
- Prevents formation of black sludge/asphaltene
- Restores thermal and oxidation stability of ULSD fuels
- Eliminates formation of carbon deposits in High-Pressure Fuel Injection systems
- Restores horsepower lost due to the formation of deposits
- Vastly extends filter life
- Contains LYVAN which replaces lubricity lost due to the removal of sulfur in the production of **Ultra Low Sulfur Diesel Fuels**
- **Clean-Up** of fuel injection system per **XUD9 specification, Keep Clean** per **DW10** and **IDID specification**
- Restores fuel economy to new engine performance levels
- Compatible with bio-diesel fuel and blends
- Elimination of steel corrosion caused by ULSD
- Contains Anti-Icer and Moisture Control to eliminate water problems

**THIS PRODUCT DOES NOT CONTAIN ALCOHOL**

#### BULK TREATMENT RATIO

<b>1-425</b>	<p><i>To keep clean and prevent build-up of carbon or soot and vastly extend filter life of equipment that is clean or new.</i></p> <p><b>Increases Cetane points to 50 or more</b></p>
--------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

*Meets NCWM definition of PREMIUM DIESEL at above ratios*

#### CONTAINER SIZES

- ⇒55 Gallon Drums
- ⇒275 Gallon Totes
- ⇒Bulk



**MEETS AND EXCEEDS JOHN DEERE & STANADYNE REQUIREMENTS FOR ADDED LUBRICITY IN ULTRA LOW SULFUR DIESEL FUELS**